



NOTES:

1. Rating: 600V 35A
2. Insulation Withstands Voltage: AC 2200V at 1 minute.
3. Insulation Resistance: 500M Ω or more at DC500V
4. Using Temperature Range: -40°C~+105°C
5. Screw Torque Value: 8 kgf-cm
6. Suitable Electric Wire: AWG 22~10
7. RoHS compliance

Normal Geometric Tolerancing

—	/ /	\equiv	\perp
0 to 100	0.2	0 to 10	0.2
over 100 to 150	0.3	over 10	0.3
over 150	0.5		
Total Pitch Tolerances		Normal dimension Tolerances	
0<U<=30	± 0.20	0~30	± 0.25
30<U<=53	± 0.25	over 30~53	± 0.30
53<U<=70	± 0.30	over 53~70	± 0.35
70<U<=90	± 0.35	over 70~90	± 0.44

REV.	CONTENT	CHK.	DATE

DWG.	LWF	DATE	09.08.11	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	3:1		
APP.		DATE					

ITEM	NAME OF PART	MATERIAL	NOTES
1	HOUSING 1	PA66	UL94-V2 GRAY
2	HOUSING 2	PA66	UL94-V2 GRAY
3	HOUSING 3	PA66	UL94-V2 GRAY
4	HOUSING 4	PA66	UL94-V2 GRAY
5	SOLDER POST	COPPER ALLOY	Tin Plated
6	SCREW	STEEL	M3/Zn Plated
7	WIRE CAGE	STEEL	Zn Plated

DINKLE
ENTERPRISE CO., LTD

PPAC-4

DWG NO. SP-03-PPAC4000