


Spring-cage connection terminal block-
UJ5-4RDX(5 × 20) -421040




Spring-cage connection terminal block , rated voltage:250V , Max. operating current:6.3A, connection method:spring-cage connection, number of connection : 2 , crimping range : 0.2 mm² -6mm² , AWG : 24-10 , thickness:6.2mm , height:60.5mm , color : black , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	60
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	6
Color	black
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	250
Rated current(A)	6.3
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Parameter	Data
	RoHS

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	10
Solid conductors(mm ²)	0.2-6
Solid conductors AWG	24-10
Stranded conductors(mm ²)	0.2-4
Stranded conductors AWG	24-10
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	61.8
Thickness(mm)	6.2
Height(mm)	60.5