


Spring-cage connection terminal block-
UJ5-2.5WM/2 × 2JD-421144





Terminal block, connection methods:spring-cage connection, number of connection:2, crimping range:0.08mm² -2.5mm² , AWG : 28-14, thickness10mm, height30.2mm, color: yellow green, mounting rail:TH35-7.5、 TH35-15.

Product parameter

Parameter	Data
Packing unit(pcs)	98
NW per piece(g)	7.5
Layers	1
Number of connections	2
Rated cross section(mm ²)	2.5
Color	Yellow green
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	/
Rated current(A)	/
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	9
Solid conductors(mm ²)	0.08-2.5
Solid conductors AWG	28-14
Stranded conductors(mm ²)	0.08-2.5
Stranded conductors AWG	28-14
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-2

Dimension

Parameter	Data
Width(mm)	32.2
Thickness(mm)	10
Height(mm)	30.2