

Data sheet

Commercial Art.No.: 99.719.0000.7

Cable assembly RST20i3K1-S

RST20i3/2 mains connection cable RST20i3 male - female Schuko, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H07RN-F, length 0.5m, cross section 1.5mm², coding color black



Commercial Art.No.	99.719.0000.7
EAN	4049088458514
Order Unit	4

Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	black

Model

type of construction	Shrinkage tube
Connection type	Crimp
Nominal cross section conductor	1.5 mm ²
sheath strip length	35 mm
Preparation of conductor ends	ultrasonically compressed wire ends
Cable type	H07RN-F
Cable color	black
Cable diameter min.	9.6 mm
Cable diameter max.	10 mm
Version of cable	male - female CEE 7/4
Type of cord set	mains connection cable
Version cable end 1	SchuKo socket
Version cable end 2	male
Shielded	No

Material

Surface finish	Silver-plated
----------------	---------------

halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C
Fire load	0.397 kWh

Dimensions

Total length	0.5 m
--------------	-------

Note

Note	The total length may vary up to + / - 3 %.
------	--

Classification

ECLASS 11	
ECLASS 8.1	27440604
ETIM 7.0	EC002587
ETIM 6.0	EC002587
ETIM 5.0	EC002587
ETIM 4.0	EC002587

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1