



Model Type: EC-12025xxxx

Dimension : 120 x 120 x 25 mm

	Voltage	5V		12V	24V
				✓	
	Fan Speed	L		M	H
		1800		2000	2200
	Certificate	UL		CE	TUV
		✓		✓	✓
Bearing Type	Sleeve	1 Ball	2 Ball	EL	
	✓	✓	✓	✓	

Model Type: Strong Frame EC-12025II

Dimension : 120 x 120 x 25 mm

	Voltage	5V			12V	24V	
					✓	✓	
	Fan Speed	SL	LL	L	M	H	HH
		1400	1700	2000	2300	2600	2900
	Certificate	UL			CE	TUV	
		✓			✓	✓	
Bearing Type	Sleeve			1 Ball	2 Ball	EL	
	✓			✓	✓	✓	

Model	Voltage VDC	Current AMP	Input Watts	Fan Speed RPM	AirFlow (Max) CFM	Pressure InchH ₂ O	Noise dBA	Life Hour
EC12025H12B	12	0.33	3.96	2200	78.41	0.11	<39	50000
EC12025H12C								35000
EC12025H12S								25000
EC12025H12E								40000
EC12025M12B	12	0.28	3.36	2000	72.94	0.1	<36	50000
EC12025M12C								35000
EC12025M12S								25000
EC12025M12E								40000
EC12025L12B	12	0.25	3	1800	68.96	0.09	<34	50000
EC12025L12C								35000
EC12025L12S								25000
EC12025L12E								40000
Strong Frame 12025II								
EC12025HH24B	24	0.44	10.56	2900	106.46	0.19	<45.7	50000
EC12025HH24C								35000
EC12025HH24S								25000
EC12025HH24E								40000
EC12025H24B	24	0.32	7.68	2600	91.39	0.17	<43.4	50000
EC12025H24C								35000
EC12025H24S								25000
EC12025H24E								40000
EC12025M24B								50000

EC12025M24C	24	0.28	6.72	2300	85.53	0.15	<40.7	35000
EC12025M24S								25000
EC12025M24E								40000
EC12025L24B	24	0.24	5.76	2000	70.4	0.11	<37.7	50000
EC12025L24C								35000
EC12025L24S								25000
EC12025L24E								40000
EC12025L24B	24	0.2	4.8	1700	62.49	0.09	<34.1	50000
EC12025L24C								35000
EC12025L24S								25000
EC12025L24E								40000
EC12025SL24B	24	0.16	3.84	1400	53.4	0.07	<28.3	50000
EC12025SL24C								35000
EC12025SL24S								25000
EC12025SL24E								40000
EC12025HH12B	12	0.85	10.2	2900	106.46	0.19	<45.7	50000
EC12025HH12C								35000
EC12025HH12S								25000
EC12025HH12E								40000
EC12025H12B	12	0.65	7.8	2600	91.39	0.17	<43.4	50000
EC12025H12C								35000
EC12025H12S								25000
EC12025H12E								40000
EC12025M12B	12	0.4	4.8	2300	85.53	0.15	<40.7	50000
EC12025M12C								35000
EC12025M12S								25000
EC12025M12E								40000
EC12025L12B	12	0.32	3.84	2000	70.4	0.11	<37.7	50000
EC12025L12C								35000
EC12025L12S								25000
EC12025L12E								40000
EC12025LL12B	12	0.24	2.88	1700	62.49	0.09	<34.1	50000
EC12025LL12C								35000
EC12025LL12S								25000
EC12025LL12E								40000
EC12025SL12B	12	0.16	1.92	1400	53.4	0.07	<28.3	50000
EC12025SL12C								35000
EC12025SL12S								25000
EC12025SL12E								40000

E--EL bearing, B -- Two ball bearing , C -- One ball One sleeve bearing, S -- Sleeve bearing