


CPDL4



4 sq.mm Double Level Push in Terminal Blocks

CPDL4 is a double level Terminal Block used in high density wiring applications.

TECHNICAL DATA

| | |
|------------------------|-----------------------|
| Rated Voltage | 500 V |
| Rated Current | 28 A |
| Housing Material | Polymide |
| Standard Colour | Grey |
| Product Function | Double Level |
| Wire Entry Orientation | Top |
| Mounting Possibility | DIN 35/DIN 35-15 Rail |
| Rated Surge Voltage | 8 KV |
| Pollution Degree | 3 |

CONNECTION DATA

| | |
|---|---------------------|
| Conductor Cross Section Stranded min. | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 4 mm ² |
| Conductor Cross Section AWG/Kcmil min | 24 AWG |
| Conductor Cross Section AWG/Kcmil max | 10 AWG |
| Conductor Cross Section Stranded with Ferrule/Lug min | 0.2 mm ² |
| Conductor Cross Section Stranded with Ferrule/Lug max | 4 mm ² |
| 2 Conductors with same Cross Section Stranded min | 0.2 mm ² |
| 2 Conductor with same Cross Section Stranded max | 2.5 mm ² |
| Conductor Cross Section Solid min | 0.2 mm ² |
| Conductor Cross Section Solid max | 6 mm ² |
| 2 Conductors with same Cross Section Stranded with TWIN Ferrule/Lug min | 0.2 mm ² |
| 2 Conductor with same Cross Section Stranded with TWIN Ferrule/Lug max | 0.5 mm ² |
| Stripping Length | 11 mm |
| Internal Cylindrical Gauge | B3 |

DIMENSIONS

| | |
|----------------------------------|---------|
| Height with DIN 35 x 15 mm rail | 57 mm |
| Height with DIN 35 x 7.5 mm rail | 49.6 mm |
| Length | 81.6 mm |
| Width (Thickness) | 6 mm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|----------|---|-----------|
| CPDL4 | 4 sq.mm 2 Level Compact Push In Terminal Block in Grey Colour | 50 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|---------------|---|-----------|
| | CA701-1M | Din 35 Rail unslotted 1 meter | 50 |
| | CA701-2M | Din 35 Rail unslotted 2 meter | 50 |
| | CA701-2M-S | Din 35 Rail slotted 2 meter | 50 |
| | CA701-1M-S | Din 35 Rail slotted 1 meter | 50 |
| | CA701-15-1M | Din 35 Rail 15 deep unslotted 1 meter | 50 |
| | CA701-15-1M-S | Din 35 Rail 15 deep slotted 1 meter | 50 |
| | CA701-15-2M | Din 35 Rail 15 deep unslotted 2 meter | 50 |
| | CA701-15-2M-S | Din 35 Rail 15 deep slotted 2 meter | 50 |
| | CA103 | EndClamp in Polyamide suitable for Din 35/Din 35-15 rails | 50 |
| | CA104 | EndClamp in Polyamide suitable for Din 35/Din 35-15 rails | 50 |
| | JX4/2 | Shorting Link for 6 mm wide TB | 100 |
| | JX4/3 | Shorting Link for 6 mm wide TB | 50 |
| | JX4/4 | Shorting Link for 6 mm wide TB | 50 |
| | JX4/5 | Shorting Link for 6 mm wide TB | 50 |
| | JX4/8 | Shorting Link for 6 mm wide TB | 10 |
| | JX4/10 | Shorting Link for 6 mm wide TB | 10 |
| | JX4/16 | Shorting Link for 6 mm wide TB | 10 |
| | CA509/K6 | Blank Marking Tag | 100 |
| | SCS0.5/3 | Electricians Screwdriver for slotted screws | 10 |
| | EPCPDL4 | End Plate in Grey Colour | 50 |
| | MC6 | MARKER CARD 6MM PITCH WITH 72 TAGS | 10 |


APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CPDL4



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

| STANDARDS | UL 1059 | IEC/EN60947-7-1 |
|---------------------------------------|----------------|------------------------|
| Conductor Cross Section Stranded min. | 24 AWG | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 10 AWG | 4 mm ² |
| Rated Voltage | 300 V | 500 V |
| Rated Current | 28 A | 28 A |