


Barrier screw terminal block-UTD-63-391006







Barrier screw terminal block , rated voltage:660V , Max. operating current:90A, connection method : screw connection , number of connections : 2 , crimping range : 5.5mm² -22mm² , AWG : 10-4 , thickness:19.5mm , height:38mm , color : Black , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	22
Color	black
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	90
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

Parameter	Data
	
Certification logo	

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M6 × 14
Stripping length(mm)	/
Tightening torque	4-5
Solid conductors(mm ²)	5.5-22
Solid conductors AWG	10-4
Stranded conductors(mm ²)	5.5-22
Stranded conductors AWG	10-4
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	54
Thickness(mm)	19.5
Height(mm)	38