

Bridge Rectifiers

Features



- UL recognition, file #E230084
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package:** KBL
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body



■ Maximum Ratings ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Device marking code			KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	400	600	800	1000
Average Rectified Output Current @60Hz sine wave, R-load, Without heatsink $T_a=40^\circ\text{C}$	I_O	A	4						
Surge(Non-repetitive)Forward Current @60Hz half-sine wave, 1 cycle, $T_a=25^\circ\text{C}$	I_{FSM}	A	120						
Current Squared Time @ $1\text{ms} \leq t \leq 8.3\text{ms}$, $T_j=25^\circ\text{C}$, Rating of per diode	I^2t	A^2S	59.8						
Storage Temperature	T_{stg}	$^\circ\text{C}$	-55 ~+150						
Junction Temperature	T_j	$^\circ\text{C}$	-55 ~+150						

■ Electrical Characteristics ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Maximum instantaneous forward voltage drop per diode	V_F	V	$I_{FM}=4\text{A}$	1.05						
Maximum DC reverse current at rated DC blocking voltage per diode	I_{RRM}	μA	$V_{RM}=V_{RRM}$	10						



KBL4005 THRU KBL410

■ Thermal Characteristics ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Thermal Resistance	Between junction and ambient,	$R_{\theta J-A}$	$^\circ\text{C}/\text{W}$	21 ⁽¹⁾						
	Between junction and lead	$R_{\theta J-L}$		2.4 ⁽²⁾						





Notes

- (1) Thermal resistance from junction to ambient with units mounted on 3.0*3.0*0.11" thick(7.5*7.5*0.3cm) aluminum plate
- (2) Thermal resistance from junction to lead with units mounted on P.C.B.at 0.375"(9.5mm)lead length and 0.5*0.5"(12*12mm) copper pads

■ Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
KBL4005~KBL410	A1	Approximate 4.54	500	500	4000	Paper Box


■ Characteristics (Typical)





KBL4005 THRU KBL410

■ Outline Dimensions



KBL		
Dim	Min	Max
A	13.7	15.7
B	15.2	16.3
C	1.2	1.3
D	16	/
E	4.6	5.6
F	5.5	6.5
G	1.8	2.4
H	18.5	19.5



KBL4005 THRU KBL410

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.