

Spring-cage connection terminal block- UJ5-2.5/3TP-421237





Terminal block, Rated voltage(V):380V, Rated current:24A, connection methods: spring-cage connection, number of connection: 3, crimping range:0.1mm² -2.5mm² , thickness 21.9mm, height 15.2mm, color grey.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	/
Layers	1
Number of connections	3
Rated cross section(mm ²)	2.5
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	380
Rated current(A)	24
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	8
Solid conductors(mm ²)	0.1-2.5
Solid conductors AWG	/
Stranded conductors(mm ²)	0.1-2.5
Stranded conductors AWG	/
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-2

Dimension

Parameter	Data
Width(mm)	35.1
Thickness(mm)	21.9
Height(mm)	15.2