



| | | 尺寸公差(mm) | | | |
|------------------------------------|-------------------|----------|-------|-------|-------------|
| | | 0 | >30 | >60 | >100 |
| Rated current | 300V/A | ~ | ~ | ~ | ~ |
| Rated voltage | 300V | 30 | 60 | 100 | 150 |
| Coil/Contact dielectric voltage | 2000V/S | ~ | ~ | ~ | >150 |
| Dielectric voltage between contact | 2000V/S | ±0.20 | ±0.30 | ±0.50 | ±0.70 ±1.00 |
| Screw torque | 1.0Nm | | | | |
| External connection wire | 20-14/0.5-2.5W | | | | |
| Ambient temperature | G/mm ² | | | | |
| Key controlled symbol | -40~+65℃ | | | | * |
| Conform to RoHS | | | | | |

Printing for laser marking/printing content is clear ,no broken line/rect
 Seal literal reference according to the foot position in the drawing

| REV | ECN | DESCRIPTION | DRAFT | DATE |
|-----|-----|-------------|-------|------|
| | | | | |

| | | | | | | |
|-----------|-------------|--|-----------------|--------|----------|-----------|
| NO. | 1 | DPYF14A-3-00A(H)-N | 30019000027 | 1 | | |
| MATERIAL: | / | DESCRIPTION | MATERIAL NO. | QTY | MATERIAL | NOTES |
| MAT. NO.: | 30020000046 | | | | | |
| STATUS: | / | | | | | |
| APPD.: | | Description: NINGBO DEGSON ELECTRICAL CO., LTD 宁波高松电子有限公司 | | | | |
| CHKD.: | | | | | | |
| DRAFT: | / | DRAWING NO.: | 30000354 | REV | TO-1 | |
| | | TYPE: | PRODUCT DRAWING | SCALE: | 1:1 | SHEET 1/1 |