

Economical relay module-UDK-PLC-RI 48Vdc E-328038



Relay coupling, voltage input: 48V, current input: about 8mA, connection methods: screw connection, pollution degree: 2, AWG: 26-14, current output: 6A, width 82mm, thickness 6.2mm, color: grey, mounting rail: TH35-7.5, G32-15.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	/
Cross section(mm ²)	0.14-2.5
Color	grey
Materials	PA66
Flame retardant rating	V0
Voltage input(V)	48V
Current input(mA)	about 8mA
Insulation material temperature	-40 ~ +125
Connection methods	screw connection

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data

Parameter	Data
Connection methods	screw connection
Current output (A)	6A
Upper switching voltage (V)	250V
Rated power(W)	140
Coils/contacts	4000V
Contact material	AgNi
Resistive load	1500V
Ambient temperature ()	-25 ~ +60
Storage temperature (Storage/transportation) ()	-30 ~ +80
Relative humidity	5% ~ 85%
Connection in acc. with standard	IEC 60947-5-1
Pollution degree	2

Dimension

Parameter	Data
Width(mm)	82
Thickness(mm)	6.2
Height(mm)	80.2