


Category: 插拔式端子-插头/Plug-in terminal-plug

Product name: MC-RU5.08SVXX-F-0001

Product Description: 5.08mm , 320V , 16A CE



### Product Picture



### 基本信息 /Basic Information

产品型号 SUPU ID	MC-RU5.08SVXX-F-0001
产品间距 Pitch	5.08mm
产品层数 Number of levels	1
产品位数 Number of connections	2P-24P
接线方式 Connection method	-

防护等级 Protection Level	IP20
工作温度 Work temperature	-40~+105°C

## IEC数据 /IEC Data

额定电流 Rated Current	16A		
额定电压 Rated Voltage	320V		
过压类别 Overvoltage category	III	III	II
污染等级 Pollution degree	3	2	2
额定冲击电压 Rated impulse voltage	4KV	4KV	4KV
额定电压 Rated Voltage	320V	320V	630V
硬导线截面积 Conductor cross section solid	-		
柔性导线截面积 Conductor cross section flexible	-		
柔性导线截面积，带绝缘管套 Conductor cross section flexible,with furrule	-		
锁线螺钉规格 Locking screw Specification	-		
额定扭矩 Rated Torque	-		
固定螺钉规格 Fixed Screw Specification	M2.5		
额定扭矩 Rated Torque	0.3N.M		
剥线长度 Stripping length	-		

## UL数据 /UL Data

使用组别 Use group	B	C	D
额定电流 Rated Current	16A	-	10A

额定电压 Rated Voltage	250V	-	300V
额定接线容量 Rated cross section	-		

## 材料信息 /Material Data

绝缘材料 Insulation material	PA66		
绝缘材料组别 Insulation material group	I		
阻燃等级，符合UL94 Flame retardant grade, UL94 compliance	V0		
导体材料 Contact material	Copper alloy		
导体表面镀层 Surface characteristics	Sn,Plated		

## 产品认证 /Product Certification

认证图标  
Certificate



UL证书号  
UL file No.

VDE证书号  
VDE No.

TUV证书号  
TUV No.

Ningbo Supu Electronics Co.,Ltd

Zip code: 315303

Fax: +86 574-63288170

E-mail : askme@supu.cn

Address: No. 625, Kandun Town Street, Cixi  
City, Zhejiang Province

Switchboard: +86 574-63288158

E-mail : askme@supu.cn

Service Hotline: 400-626-6336



Code

