


Optocoupler-UDK-PLC-O 60Vdc-317006



Optocoupler, input voltage: 60V, input current: $\leq 4\text{mA}$, connection methods: screw connection, pollution degree: 2, AWG: 26-14, input current: 0~3A, width 80mm, thickness 6.2mm, color: grey, mounting rail: TH35.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	/
Cross section(mm^2)	0.14-2.5
Color	grey
Materials	PA66
Flame retardant rating	V0
Voltage input(V)	60V
Current input(mA)	≤ 4
Insulation material temperature	$-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
Connection methods	screw connection

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data

Parameter	Data
Connection methods	screw connection
Output current (A)	0~3A
Output Voltage(V)	5-24V
Rated impulse voltage	4KV
Turn-on time	$\leq 100\mu s$
Turn-off time	$\leq 100\mu s$
Voltage drop at max. load	≤ 1
Ambient temperature (°C)	-25°C~+40°C
Storage temperature (Storage/transportation) (°C)	-30°C~+80°C
Relative humidity	5%~85%
Connection in acc. with standard	IEC 60947-5-1
Pollution degree	2

Dimension

Parameter	Data
Width(mm)	80
Thickness(mm)	6.2
Height(mm)	94