

USP-75MFN-24DN- 462213




Switching power supply, DC output voltage: 24V, output voltage accuracy: $\pm 1\%$, rated output current: 3.2A, output current range: 0-3.2A, output power: 76.8W, width 32mm, height 125mm.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	350

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	24V
Output voltage accuracy	$\pm 1\%$
Rated output current(A)	3.2A
Output current range	0~3.2A
Output power	76.8W
Ripple and noise	120mVp-p
Setting range of voltage,DC	24-28V
Hold up time	12ms/115VAC,60ms/230VAC
Efficiency	89%
Shock current	Cold start current45A/115VAC , 25A/230VAC
Working temperature	-30 ~ +70
Ambient temperature	-40 ~ +85

Parameter	Data
(storage/transportation) ()	
Insulation impedance	100M Ohms/500VDC/25 /70%RH
Safety standards	I/P-O/P:4KVAC
EMC standards	IS13252(Part1)&EN62368-1,UL/IEC 62368-1

Dimension

Parameter	Data
Width(mm)	87.5
Thickness(mm)	32
Height(mm)	125