


尺寸 Size: 160mm × 160mm × 62mm  
 风量 Airflow: 220-275CFM  
 重量 Weight: 1200g  
 噪音 Noise: 50-59dB(A)  
 风叶 Impeller Material: PBT UL94-V0 Reinforced Plastic  
 外框 Frame: Aluminum Alloy  
 端子 Terminals: 0.5mm  
 引线 Lead Wire: AWG#22 UL 1569(Optional)  
 马达 Motor: Capacitor-Run Induction Motor  
 温度范围 Operating Temperature: -10°C~+65°C



产品型号 Model	轴承型式 Bearing System	电压 Voltage VAC	频率 Freq. Hz	电流 Current A	功率 Power W	转速 Speed RPM	噪音 Noise dB(A)	风量 Air Flow CFM	相数 Phase	电容 Capacitor μF/VAC
G16062HA,B-C-7P	Ball	100/125	50/60	0.38/0.37	37/39	2750/3050	54/59	240/275	1	3.3/250
G16062HA,B-C-7P		200/240	50/60	0.15/0.17	30/36	2750/3050	54/59	240/275	1	1/500
G16062HA,B-C-7P	Ball	380/420	50/60	0.08/0.09	30/35	2300/2600	50/54	220/225	3	—
G16062HA,B-C-7P		380/420	50/60	0.1	30/35	2300/2600	50/54	220/255	1	0.33/500
G16062MA,B-C-7P	Ball	100/125	50/60	0.35	35	2300/2600	50/54	220/225	1	3.3/250
G16062MA,B-C-7P		200/240	50/60	0.18	35	2300/2600	50/54	220/255	1	1/500

