


Spring-cage connection terminal block- UJ5-35 - 421007



Spring-cage connection terminal block , rated voltage:800V, Max. operating current:125A, connection method:spring-cage connection, number of connection : 2 , crimping range : 2.5 mm² -35mm² , AWG : 14-2 , thickness:16.2 mm , height:58.6mm , color : grey , mounting type : TH35-7.5、TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	10
NW per piece(g)	77.3
Layers	1
Number of connections	2
Rated cross section(mm ²)	35
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	800
Rated current(A)	125
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

Parameter	Data
	
Certification logo	CCS
Certification logo	IECE_x
Certification logo	cUL[®] US
Certification logo	
Certification logo	
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	25
Solid conductors(mm ²)	2.5-35
Solid conductors AWG	14-2
Stranded conductors(mm ²)	2.5-35
Stranded conductors AWG	14-2

Parameter	Data
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	100
Thickness(mm)	16.2
Height(mm)	58.6