


Barrier screw terminal block-
UTD-24 / 2-2- 391013



Barrier screw terminal block , rated voltage:660V ,
Max. operating current:24A, connection
method : screw connection , number of
connections : 4 , crimping
range : 0.75mm² -2.5mm² , AWG : 18-14 , t
hickness : 9.5mm , height:42mm , color : Black
, mounting
type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	2
Number of connections	4
Rated cross section(mm ²)	2.5
Color	black
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	24
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M3.5 × 8
Stripping length(mm)	/
Tightening torque	1.0-1.3
Solid conductors(mm ²)	0.75-2.5
Solid conductors AWG	18-14
Stranded conductors(mm ²)	0.75-2.5
Stranded conductors AWG	18-14
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	58
Thickness(mm)	9.5
Height(mm)	42