


Screw clamping terminal block-UKJ-
W2.5/2 × 2JD- 431010



Screw clamping terminal block, connection method : screw connection , number of connections : 4 , crimping range : 0.5mm² -6mm² , thickness:5.2mm , height:62.3mm , color : yellow-green , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	40
NW per piece(g)	0.78
Layers	2
Number of connections	4
Rated cross section(mm ²)	4
Color	yellow-green
Insulation material	PA
Flame retardant grade (UL94)	V0
Temperature of insulation material	-40 ~ +125
Wire feed	Both sides of the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M2.5
Stripping length(mm)	10
Tightening torque	0.4-0.6
Solid conductors(mm ²)	0.5-4
Stranded conductors(mm ²)	0.5-2.5
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	69.4
Thickness(mm)	5.2
Height(mm)	62.3