

## Data sheet

Commercial Art.No.: 78.019.4056.0

Modular insert MOD STX 2 05



Commercial Art.No.	78.019.4056.0
EAN	4049088382260
Order Unit	10

Certificates / Approvals



## Technical data

### Classification

ECLASS 11	
ECLASS 8.1	27440205
ETIM 7.0	EC000438
ETIM 6.0	EC000438
ETIM 5.0	EC000438
ETIM 4.0	EC000438

### General

Model	Pin insert
Inflammability class of insulation material acc. with UL94	V0
Color	Grey
Mating cycles	500
Pollution degree	3
Modular version	yes
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

### Connection Data

Connection type	Crimp
Number of poles	4
Plus switching contacts	0
Number of pole for rated current 2	0
Number of pole for rated current 3	0
Protective contact	No

### Technical Data UL/CSA

Rated voltage according to UL/CSA	
-----------------------------------	--

Rated current according UL	10 A
----------------------------	------

**Model**

With housing	No
--------------	----

**Technical Data DIN EN 61984**

Nominal voltage	50 V
Nominal current	10 A
Rated impulse voltage	0.8 kV

**Product compliance**

REACH-SVHC conformity status	Compliant
------------------------------	-----------