


Spring-cage connection terminal block-
UJ1-4/2JD - 021008



Spring-cage connection terminal block , rated voltage:/ , Max. operating current:/, connection method : Spring-cage connection , number of connections : 2 , crimping range : 0.5mm² -4mm² , thickness : 6.2mm , height:36.4mm , color : green , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	4
Color	green
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	/
Rated current(A)	/
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	8
Solid conductors(mm ²)	0.5-4
Solid conductors AWG	/
Stranded conductors(mm ²)	0.5-4
Stranded conductors AWG	/
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	52
Thickness(mm)	6.2
Height(mm)	36.4