

Data sheet

Commercial Art.No.: 73.326.4028.0

Bottom BAS GUT GX 16H A

Bottom-base revos basic made of aluminum, with double locking lever for terminal adapters mounted on the rear, open, high version, 16-poles



Commercial Art.No.	73.326.4028.0
EAN	4015573229419
Order Unit	1

Technical data

General

Housing material	aluminum
Color	Grey
Surface	With powder coating
Degree of protection (IP)	IP54
UV resistant	yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

Construction	16
Locking mechanism	Double locking levers
Cable entry	None
Type of cable	None
With cable screw gland	No
Thread size PG	
Hinged lid	No
EMC-version	No
Length	113 mm
Width	43 mm
Height	27.9 mm

Classification

ECLASS 11	
ECLASS 8.1	27440202
ETIM 7.0	EC000437
ETIM 6.0	EC000437

Product compliance

REACH-SVHC conformity status	Compliant
------------------------------	-----------

Fits with

Commercial Art.No.:	Article-type description:	Description:
73.100.4053.0	Multipole adapter HD BAS WL 40 2,5 25	Multipole adapter revos HD 250V/10A 40 pole + ground, female insert, ground left
73.105.4053.0	Multipole adapter HD BAS WR 40 2,5 25	Multipole adapter revos HD 250V/10A 40 pole + ground, female insert, ground right
73.110.4053.0	Multipole adapter HD SAS WL 40 2,5 25	Multipole adapter revos HD 250V/10A 40 pole + ground, male insert, ground left
73.115.4053.0	Multipole adapter HD SAS WR 40 2,5 25	Multipole adapter revos HD 250V/10A 40 pole + ground, male insert, ground right