

CP-371

CrimpPro Crimp Frame Only (236mm)





PRO-CRIMPER SERIES

Pro'sKit Tool



PRO-CRIMPER SERIES

Pro'sKit
ISO 9001
CERTIFIED

MADE IN TAIWAN

Description










CP-371 is a multifunctional crimping tool with snap matrix, that is designed to crimp a wide range of connectors. The smooth ratcheting mechanism of CP-371 will ensure positive connections each time and keep the metal frame and its built-in dies rigid and durable.

Features














- Right angle head design prevents awkward wrist bending during operation.
- Interchangeable die with thumbscrew.
- Made from high quality carbon steel with black oxide finish for corrosion resistance and durability.
- Energy saving ratcheting mechanism requires less handle force and ensures the crimping quality.
- Safety crimp release helps eliminate rejected terminations due to incorrect positioning.
- Ergonomically shaped non-slip handles for user comfort.

Specifications

Material	OAL (mm)	Individual packing
S45C	210	Blister card

Complete tool with die		Replacement die set	Hex size	Description
CP-371				Frame Only
CP-371A		CP-236DE	AWG 22/20/18/16/14/12 DIN 0.5/0.75/1.0/1.5/2.5/ 4.0mm ²	 Pin Terminal Insulated or Non-insulated Ferrules
CP-371B		CP-236DR	AWG 22-18/16-14/12-10 JIS 1.25/2.0/5.5 mm ²	 Vinyl Insulated W/O Copper Sleeve
CP-371C		CP-236DN	AWG 20-18/16-14/12-10/ 8 DIN 1.5/2.5/6/10mm ² JIS 1.25/2.0/5.5/8mm ²	 Non-insulated Terminal
CP-371D		CP-236DF	AWG 22-18/16-14	 Insulated Flag

CP-371E		CP-236DF1	AWG 22-18/16-14	Uninsulated Flag
CP-371F		CP-236DC	AWG 20-18/16-14/12-10	 Interlocking 2.5 & Non-insulated
CP-371G		CP-236DM5		Molex 8P8C/RJ45 Plug & Cable O/D Around ø5.2
CP-371H		CP-236DM6		Molex 8P8C/RJ45 Plug & Cable O/D Around ø5.8
CP-371I		CP-236DQ		HC-002-8S 8P8C/RJ45 Shielded Plugs (Hirose Type Short Body)
CP-371J		CP-236DQ1		Hirose 8P8C/RJ45 Shielded Plugs (Hirose Type)
CP-371K		CP-336DJ	.042", .068", .078", .128", .151", .178" (1.07/1.72/ 1.98/3.25/3.84/4.52mm)	 RG 174, 179 Belden 8218 Fiber Optic
CP-371L		CP-336DK4	.100", .128", .190", .213" (2.54/3.25/4.83/5.41mm)	 RG 58, 174
CP-371M		CP-336DV	.043", .069", .100", .128", .151", .213" (1.09/1.75/ 2.54/3.25/3.84/5.41mm)	 SMA, SMB, SMC, MCX
CP-371N		CP-336DG	.043", .068", .100", .137", .213", .255" (1.09/1.72/ 2.54/3.48/5.41/6.48mm)	 RG 58, 59, 62 , 174 Fiber Optic
CP-371O		CP-336DA4	.255", .187", .068", .213" (6.48/4.75/1.72/5.41mm)	 RG 58, 59, 62 , 174
CP-371P		CP-336DA	.256", .068", .213" (6.50/ 1.72 / 5.41mm)	 RG 58, 59, 62
CP-371Q		CP-336DI	.255", .211", .093", .067", 0.315" (6.48/5.36/2.36/ 1.70/8.00mm)	 RG 58, 59, 6, 174

CP-371R		CP-336DC	.256",.319",.068",.213" (6.50/8.10/1.72/5.41mm)	 RG 58,59,62 ,6
CP-371S		CP-336DP1	.255",.213",.098",.068", .321"(6.48/5.41/2.49/ 1.72/8.15mm)	 RG 58,59,62 ,6
CP-371T		CP-336DH1	.255",.320",.350" (6.48 /8.13/8.90mm)	 CATV F Connectors RG 59,6
CP-371U		CP-336DC1	.068",.216",.324",.360" (1.72/5.49/8.23/9.14 mm)	 F-59,62,6
CP-371V		CP-336DK5	.080",.100",.429" (2.03 /2.54/10.90mm)	 RG 11,174
CP-371W		CP-336DY1	.069", .218" (1.75/5.54 mm)	 RG 58 OVAL TYPE
CP-371X		CP-236D 8PAMP	AMP 8P8C/RJ45(Secondary strain relief)	