

USP-75MFN-12DN- 462212




Switching power supply, DC output voltage: 12V, output voltage accuracy: $\pm 2\%$, rated output current: 6.3A, output current range: 0-6.3A, output power: 75.6W, width 32mm, height 125mm.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	350

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	12V
Output voltage accuracy	$\pm 2\%$
Rated output current(A)	6.3A
Output current range	0~6.3A
Output power	75.6W
Ripple and noise	80mVp-p
Setting range of voltage,DC	12-14V
Hold up time	12ms/115VAC,60ms/230VAC
Efficiency	86%
Shock current	Cold start current45A/115VAC , 25A/230VAC
Working temperature	-30 ~ +70
Ambient temperature	-40 ~ +85

Parameter	Data
(storage/transportation) ()	
Insulation impedance	100M Ohms/500VDC/25 /70%RH
Voltage resistance	I/P-O/P:4KVAC
EMC standards	IS13252(Part1)&EN62368-1,UL/IEC 62368-1

Dimension

Parameter	Data
Width(mm)	87.5
Thickness(mm)	32
Height(mm)	125