



1. DISPLAY TYPE: FSTN
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
4. OPERATING TEMP: -20° --- +70° C
5. STORAGE TEMP: -30° --- +80° C
6. LCD OPERATING VOLTAGE: 8.7V VDD=3.0V
7. DRIVE METHOD: 1/65 DUTY 1/9BIAS
8. CONTROLLER: ST7567
9. BACKLIGHT: LED(White; 4 DIES) V=4V(TYPE) I=60mA
10. CONNECTOR: FPC
11. UNMARKED TOLERANCES: ±0.3mm
12. THE CONTROLLED DIMENSION MASK TO BE
13. REQUIREMENT ON ENVIRONMENTAL PROTECTION: RoHS

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SYMBOL	NC	NC	NC	NC	NC	VG	NC	NC	XV0	VO	NC	NC	VSS	VDD	SDA	SCLK	A0	RSTB	CSB	NC

DETAIL A:
9:1



B:
5:1



0.25 ± 0.05
0.25 ± 0.05

CUSTOMER APVL	CUSTOMER	DATE	TITLE
DRAWN	SCALE	MI12864J-G-8	
DFTG CHK	UNIT	mm	
ENGR CHK	APPROVAL	MODEL	
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE 1/1