


UDK-PLC-RI 230Vac/dc-HC-328056



Relay coupling, voltage input: 230V, current input: about 4.5mA, connection methods: screw connection, pollution degree: 2, AWG: 26-14, current output: 10A, width 80mm, thickness 14mm, color: grey, mounting rail: TH35-7.5 , G32-15

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	/
Cross section(mm ²)	0.14-2.5
Color	grey
Materials	PA66
Flame retardant rating	V0
Voltage input(V)	230V
Current input(mA)	about 4.5mA
Insulation material temperature	-40 ~ +125
Connection methods	screw connection

Product certification

Parameter	Data
Certification logo	
Certification logo	

Technical data

Parameter	Data
Connection methods	screw connection
Current output (A)	10A
Upper switching voltage (V)	250V
Rated power(W)	140
Coils/contacts	4000V
Contact material	AgCdo
Resistive load	1500V
Ambient temperature ()	-25 ~ +60
Storage temperature (Storage/transportation) ()	-30 ~ +80
Relative humidity	5% ~ 85%
Connection in acc. with standard	IEC 60947-5-1
Pollution degree	2

Dimension

Parameter	Data
Width(mm)	80
Thickness(mm)	14
Height(mm)	94