

## Screw clamping terminal block- UKJ-10RDN- 011342





Screw clamping terminal block , rated voltage:1000V , Max. operating current:32A, connection method : screw connection , number of connections : 2 , crimping range : 1mm<sup>2</sup> -10mm<sup>2</sup> ,thickness:17.5mm , height:54.9mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

## Product parameter

Parameter	Data
Packing unit (PCS)	21
NW per piece(g)	0.95
Layers	1
Number of connections	2
Rated cross section(mm <sup>2</sup> )	10
Color	grey
Insulation material	PA
Flame retardant grade ( UL94 )	V0
Rated voltage(V)	1000
Rated current(A)	32
Temperature of insulation material	-40 ~ +125
Wire feed	Both sides of the terminal

## Product certification

Parameter	Data
Certification logo	
Certification logo	

## Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M4
Stripping length(mm)	11
Tightening torque	1.2-1.8
Solid conductors(mm <sup>2</sup> )	1-10
Stranded conductors(mm <sup>2</sup> )	1-10
Operating temperature ( )	-40 ~ +105
Ambient temperature (storage/transportation) ( )	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

## Dimension

Parameter	Data
Width(mm)	77.7
Thickness(mm)	17.5
Height(mm)	54.9