

Spring-cage connection terminal block-
UJ1-2.5/4 - 021003



Spring-cage connection terminal block , rated voltage:660V , Max. operating current:24A, connection method : Spring-cage connection , number of connections : 4 , crimping range : 0.2mm² -2.5mm² , thickness : 5mm , height:41mm , color : grey , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	4
Rated cross section(mm ²)	2.5
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	24
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	cUL [®] US

Parameter	Data
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	7
Solid conductors(mm ²)	0.2-2.5
Solid conductors AWG	/
Stranded conductors(mm ²)	0.2-2.5
Stranded conductors AWG	/
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	50.2
Thickness(mm)	5
Height(mm)	41