

Data sheet

Commercial Art.No.: Z6.562.7456.0

Contact carrier MOD STKT 4 05



Commercial Art.No.	Z6.562.7456.0
EAN	4049088382284
Order Unit	1

Certificates / Approvals



Technical data

General

Model	Pin insert
Inflammability class of insulation material acc. with UL94	V0
Color	Grey
Mating cycles	500
Pollution degree	3
Modular version	yes
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Connection Data

Connection type	Crimp
Number of poles	4
Plus switching contacts	0
Number of pole for rated current 2	0
Number of pole for rated current 3	0
Protective contact	No

Technical Data UL/CSA

Rated voltage according to UL/CSA	
Rated current according UL	10 A

Model

With housing	No
--------------	----

Contacts

Contact material	See contacts
------------------	--------------

Surface	Silver-plated
Contact resistance	≤ 4 mOhm
Wire strip length	8 mm

Technical Data DIN EN 61984

Nominal voltage	50 V
Nominal current	10 A
Rated impulse voltage	0.8 kV

Classification

ECLASS 11	
ECLASS 8.1	27440205
ETIM 7.0	EC000438
ETIM 6.0	EC000438
ETIM 5.0	EC000438
ETIM 4.0	EC000438

Product compliance

REACH-SVHC conformity status	Compliant
------------------------------	-----------