


REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 08/23/07'	~	



SPECIFICATION

1. Insulation Resistance:1000MΩ Min.
2. Withstand Voltage:500V AC/Minute.
3. Durability:600 Cycles Min.
4. Contact resistance:50mΩ max.
5. Product Number Code:

DS1123-14 - X X X X X

- Shell Plating  
N:Nickel
- Housing Color  
T:Transparent
- Contact Plating  
0:Gold Flash 15:15u''Au  
3:3u''Au 30:30u''Au  
6:6u''Au
- No.Of Contacts  
8:8p8c
- Connector Type  
P:Plug
- Series No.  
DS1123-14

Tel: 86-574-63508787  
Fax: 86-574-63510817

(3)	BLADE	8	Copper alloy	GOLD PLATING
(2)	SHELL	1	Copper alloy	NICKEL PLATING
(1)	HOUSING	1	PC	UL94 V-0 OR 94 V-2
No.	PART NAME	Q'TY	MATERIAL	REMARK

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5'
.X	±0.38	.X	±3'
.XX	±0.25	.XX	±2'
DRAWING TYPE		CUSTOMER	
SCALE		1:1	SHEET 1 OF 1
DRAWING NO.		C-DS1123-14-XXXX	

PROJECTION	TITLE
mm	PLUG 8P8C WITH SHELL(COMBINE TYPE)
SHEET SIZE	SERIES DS1123-14 SERIES

晨翔电子有限公司  
CONNFLY CONNFLY ELECTRONIC CO. LTD