


Screw clamping terminal block-
UKJ-10/2 × 2- 011061







Screw clamping terminal block , rated voltage:660V , Max. operating current:57A, connection method : screw connection , number of connections : 4 , crimping range : 0.5mm² -16mm² , thickness:10.2mm , height:56.5mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	20
NW per piece(g)	/
Layers	2
Number of connections	4
Rated cross section(mm ²)	16
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	57
Temperature of insulation material	-40 ~ +125
Wire feed	Both sides of the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Parameter	Data
Certification logo	
Certification logo	CCS
Certification logo	IECEX
Certification logo	cUL[®] US
Certification logo	
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M4
Stripping length(mm)	11
Tightening torque	1.5-1.8
Solid conductors(mm ²)	0.5-16
Stranded conductors(mm ²)	0.5-10
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	65.3
Thickness(mm)	10.2
Height(mm)	56.5