



尺寸公差(mm)		公差	
0	>30	>60	>100
~	~	~	~
30	60	100	150
~	~	~	>150
$\pm 0.20$	$\pm 0.30$	$\pm 0.50$	$\pm 0.70 \pm 1.00$
			$\frac{\text{mm}}{\text{in}}$

  

Rated current	10A
Rated voltage	300V
Coil/Contact dielectric voltage	2000V/S
Dielectric voltage between contact	2000V/S
Screw torque	1.2Nm
External connection wire	20-14/0.5-2.5W
Ambient temperature	$G/\text{mm}^2$
Key controlled symbol	-40~+65℃
Conform to RoHS	*

Printing for laser marking/printing content is clear ,no broken line/rect  
 Seal literal reference according to the foot position in the drawing

REV	ECN	DESCRIPTION	DRAFT	DATE

1	DPTF14A-3-00A(H)-N	30019000035	1		
MATERIAL: /		SURFACE: /			
MAT.NO.: 30020000054					
STATUS: /					
APPD: /					
CHKD: /					
DRAFT: /					
DRAWING NO.: 30000362					
DESCRIPTION: <b>DEGSON</b> ® NINGBO DEGSON ELECTRICAL CO., LTD					
DPTF14A-3-00A(H)					
REV	TO-1				

1 2 3 4 5 6

REV ECN DESCRIPTION DRAFT DATE SIZE: A4 (mm) (inch) TYPE: PRODUCT DRAWING SCALE: 1:1 SHEET 1/1