


CPST1.5/4



1.5 sqmm sensor & Actuator Terminal Block

Sensor and actuator Terminal Blocks are ideal for wiring modern machine control systems.

TECHNICAL DATA

| | |
|---------------|--------|
| Rated Voltage | 250 V |
| Rated Current | 13.5 A |

CONNECTION DATA

| | |
|---------------------------------------|---------------------|
| Conductor Cross Section Stranded min. | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 1.5 mm ² |


DIMENSIONS

| | |
|----------------------------------|----------|
| Height with DIN 35 x 15 mm rail | 55.55 mm |
| Height with DIN 35 x 7.5 mm rail | 48.1 mm |
| Length | 96.5 mm |
| Width (Thickness) | 3.5 mm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|--------------------|---|-----------|
| CPST1.5/4L6-60V | 1.5 sqmm sensor and actuator Push in Terminal Block | 50 |
| CPST1.5/4 | 1.5 sqmm sensor and actuator Push in Terminal Block | 50 |
| CPST1.5/4L110-240V | 1.5 sqmm sensor and actuator Push in Terminal Block | 50 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--|----------|---------------------------------------|-----------|
|  | MC3.5 | MARKER CARD 3.5MM PITCH WITH 120 TAGS | 10 |

APPROVALS




NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

RATINGS AS PER STANDARDS

| STANDARDS | UL 1059 | IEC/EN60947-7-1 |
|---------------------------------------|---------|---------------------|
| Approvals | UL | CE |
| Conductor Cross Section Stranded min. | 24 AWG | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 14 AWG | 1.5 mm ² |
| Rated Voltage | 150 V | 250 V |

CPST1.5/4



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

Rated Current

15 A

13.5 A