

Screw clamping terminal block- UKJ-4M-011051






Screw clamping terminal block , rated voltage:500V , Max. operating current:41A, connection method : screw connection , number of connections : 2 , crimping range : 0.2mm² -6mm² , thickness:6.2mm , height:31mm , color : grey , mounting type : TH15-5.5

Product parameter

Parameter	Data
Packing unit (PCS)	90
NW per piece(g)	0.52
Layers	1
Number of connections	2
Rated cross section(mm ²)	6
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	500
Rated current(A)	41
Temperature of insulation material	-40 ~ +125
Wire feed	Both sides of the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Parameter	Data
	
Certification logo	IECE_x
Certification logo	
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M3
Stripping length(mm)	8mm
Tightening torque	0.6-0.8
Solid conductors(mm ²)	0.2-6
Stranded conductors(mm ²)	0.2-4
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	28
Thickness(mm)	6.2
Height(mm)	31