

Barrier screw terminal block-UTD-400-391011



Barrier screw terminal block , rated voltage:660V , Max. operating current:370A, connection method : screw connection , number of connections : 2 , crimping range : 150mm² -200mm² , AWG : 300-400 , thickness : 62mm , height:73.5mm , color : Black , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	200
Color	black
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	370
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

Parameter	Data
	RoHS

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M10 × 20 (bolts)
Stripping length(mm)	/
Tightening torque	25-35
Solid conductors(mm ²)	150-200
Solid conductors AWG	300-400
Stranded conductors(mm ²)	150-200
Stranded conductors AWG	300-400
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	120
Thickness(mm)	62
Height(mm)	73.5