

Features

- High reliability & Low Cost
- Proven resistance welded metal package
- Tight stability & extended temperature
- Wide frequency range from 3MHz to 100MHz
- Applications: *IoT, Consumer Electronics, HDTV, Communications, Visual Applications, etc.*
- RoHS Compliant & Pb Free


Standard Specifications

Type	6C SMD Crystal
Frequency Range	3~100 MHz
Frequency Tolerance (at 25°C)	±30ppm, or specify
Frequency Stability Over Temperature	±30ppm, or specify
Operating Temperature Range	-20~+70°C, or specify
Shunt Capacitance (C ₀)	7pF Max.
Drive Level	1~500μW (100μW Typ.)
Load Capacitance	16pF, 20pF, or specify
Aging (at 25°C)	±3ppm /year Max.
Storage Temperature Range	-55~+125°C
Packing Unit	200pcs.

Equivalent Series Resistance

Fundamental		3rd Overtone	
3~3.79MHz	200Ω Max.	27~30MHz	100Ω Max.
3.8~5.0MHz	150Ω Max.	30~50MHz	80Ω Max.
5~10MHz	80Ω Max.	50~100MHz	60Ω Max.
10~14MHz	40Ω Max.		
14~36MHz	30Ω Max.		

Dimensions [mm]
