



订货信息 Order Info

PART NUMBER	颜色 COLOR
242341	灰色 Gray
242342	橙色 Orange
242343	白灰色 Light Gray
242344	蓝色 Blue
242345	黄色 Yellow
242346	绿色 Green
242349	粉红色 Pink
242347	黄绿色 Green-yellow

基本尺寸 公差	0-3	>3-6	>6-10	>10-14	>14-18	>18-24	>24-30	>30-40	>40-50	>50-65	>65-80	>80-100	>100-120	>120-140
未标注公差参照GB/T14486	±0.08	±0.09	±0.10	±0.12	±0.14	±0.16	±0.18	±0.21	±0.24	±0.28	±0.32	±0.36	±0.41	±0.46

IEC 额定数据/IEC Rated data	
接线范围/Wire range	0.2-4.0mm ²
单股导线/Solid	0.2-4.0mm ²
软导线/Stranded	0.2-4.0mm ²
带端头软导线/Stranded with ferrules without plastic sleeve	0.2-2.5mm ²
带预绝缘端头软导线/Stranded with ferrules with plastic sleeve	0.2-2.5mm ²
剥线长度/Strip length	9-10mm
额定电压/Rated voltage	630V
额定电流/Rated current	32A
额定脉冲耐受电压/Rated surge voltage	8KV
污染等级/Pollution degree	3
过电压类别/Surge voltage category	III
其他信息/Other information	
塑件/Housing	PA66
触点材料/Contact	铜合金/Copper alloy
镀层/Coating	锡/Tin Plated
阻燃等级/Flame retardant rating	UL94-V0
使用环境温度/Usage ambient temperature	-25℃ - +70℃
储存及运输环境温度/Storage ambient temperature	-40℃ - +85℃
认证/Approval	

单位/Unit	Rev.	Name
mm	01	24234X系列带螺钉侧面接线端子 24234X series through terminal blocks with snap-in mounting feet of side-entry