

Data sheet

Commercial Art.No.: 99.710.0000.8

Cable assembly RST16i3KS-S

RST16i3/2 mains connection cable RST16i3 male - female Schuko, 3 pole, assembled with screw connection, application 250V, 16A, cable type H07RN-F, length 0.5m, cross section 1.5mm², coding color black



Commercial Art.No.	99.710.0000.8
EAN	4049088458507
Order Unit	4

Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Lockable	self-locking (unlocking by hand)
Color of coding/ contact carrier	black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	black

Model

type of construction	Cable screw gland
Connection type	screw connection
Nominal cross section conductor	1.5 mm ²
sheath strip length	35 mm
Preparation of conductor ends	ultrasonically compressed wire ends
Cable type	H07RN-F
Cable color	black
Cable diameter min.	9.3 mm
Cable diameter max.	9.7 mm
Version of cable	male - female CEE 7/4
Type of cord set	mains connection cable
Version cable end 1	SchuKo socket
Version cable end 2	male
Shielded	No

Material

Surface finish	Silver-plated
halogen free	No
Insulation components continuous temperature	100 °C
Fire load	0.444 kWh

Dimensions

Total length	0.5 m
--------------	-------

Note

Note	The total length may vary up to + / - 3 %.
------	--

Classification

ECLASS 11	
ECLASS 8.1	27440604
ETIM 7.0	EC002587
ETIM 6.0	EC002587
ETIM 5.0	EC002587
ETIM 4.0	EC002587

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1