

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	12.90~13.10	18.9~19.1
1.25~2.00	12.90~13.10	19.1~19.2
2.00~3.00	12.90~13.10	19.3~19.4

NOTES:

1. Rating:

CQC 6A 250VAC 6(8)A 250VAC
 8A/128A 250VAC T105/55
 UL CUL 10GPA 125VAC
 6GPA 250VAC T105/55
 VDE ENEC 6(4)A 250VAC T85/55
 KC 6(4)A 250VAC T85/55

2. Circuit Diagram: 2P ON-OFF

3. Terminal Strength: $\geq 80N$

4. Electrical life: ≥ 10000 cycles

5. Withstand Voltage: Withstand Voltage: 1500VAC 1min
 Terminals to Button: 3000VAC 1min


6. Leakage Current: 1mA

7. Current resistance: $\leq 50m\Omega$ (initial)

8. Insulation resistance: $\geq 100M\Omega$

9. Body Material: NYLON 66 94V-2~0

SWITCHING CIRCUIT



A4				普通公差:	深圳市华灿天禄电子有限公司								
A3				COMMON TOLERANCE :									
A2				UP TO 5	±0.20	单位	mm	投影		品名	跷板开关	比例	Free
A1				ABOVE 5 TO 30	±0.30	绘图	周金勇	核对	梁金勇	型号	RS601		
				ABOVE 30	±0.50	DRAWN BY		CHECKED BY		图号	RS601A-1010011BB		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	日期	2015.10.15	核准	周培雷	DWG NO.			