


Screw clamping terminal block-
UKHV-10 / 2 x 2- 011390




Screw clamping terminal block , rated voltage:1000V , Max. operating current:57A, connection method : screw connection , number of connections : 4 , crimping range : 0.5mm² -16mm² , AWG : 20-6 , thickness:10.2mm , height:56.5mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	20
NW per piece(g)	27.3
Layers	1
Number of connections	4
Rated cross section(mm ²)	16
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	1000
Rated current(A)	57
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data

Parameter	Data
Connection Method	Screw connection
Screw thread	M4
Stripping length(mm)	11
Tightening torque	1.5-1.8
Solid conductors(mm ²)	0.5-16
Solid conductors AWG	20-6
Stranded conductors(mm ²)	0.5-10
Stranded conductors AWG	20-6
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	65.3
Thickness(mm)	10.2
Height(mm)	56.5