


Push-in terminal block- UJ6-4/2 × 2JD - 421474



Push-in terminal block , connection method : spring connection , number of connections : 4 , crimping range : 0.2mm² -4mm² , AWG : 14-10 , thickness:6.2mm , height: 35.2mm , color : yellow-green , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	30
NW per piece(g)	15.3
Layers	1
Number of connections	4
Rated cross section(mm ²)	4
Color	yellow-green
Insulation material	PA
Flame retardant grade	V0
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

Technical data

Parameter	Data
Connection Method	Spring connection
Stripping length(mm)	13
Solid conductors(mm ²)	0.2-4
Solid conductors AWG	14-10
Stranded conductors(mm ²)	0.2-2.5
Stranded conductors AWG	14-10
Connection in acc. with standard	IEC 60947-7-1
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%

Dimension

Parameter	Data
Width(mm)	81.8
Thickness(mm)	5.2
Height(mm)	35.2