

Data sheet

Commercial Art.No.: 81.000.6210.0

Fuse module 24V DC WIPOS FM 4-10

wipos FM 4-10, Fuse Module 24 V DC, for 4 fuses 5 x 20 mm, with general fault signal (N.O. contact), Mounting on DIN Rail TS35, supply with double clamp, LED status indication per fuse, max. 10A per fuse holder, total output current of 4 fuses: max. 40 A at 23°C, Operating voltage range: 18 - 30 V DC, W x H x D: 48 x 96 x 68 mm



Commercial Art.No.	81.000.6210.0
EAN	4049088116551
Order Unit	1

Certificates / Approvals



Technical data

General

Connection type	screw connection
Rail mounting possible	yes
Operating temperature min.	0 °C
Operating temperature max.	60 °C
Degree of protection (IP)	IP20

Technical data

Fuse insert	G-fuse 5x20 mm
Rated fuse current, max.	10 A
Display	LED
General fault signal	potential-free semiconductor output
Switching output	18-30 V DC / max. 0,1 A
Connector cross section (input)	10 mm ² solid/stranded
Connector cross section (output)	0.14 - 4 mm ² solid / 0.14 - 2.5 mm ² stranded

Output

Type of output voltage	DC
Output voltage	24 V

Input

Input voltage DC min.	24 V
Input voltage DC max.	24 V

Input current, max.	40 A
---------------------	------

Dimensions

Depth	68 mm
Width	48 mm
Height	96 mm

Classification

ECLASS 11	
ECLASS 8.1	27049002
ETIM 7.0	EC002540
ETIM 6.0	EC002540
ETIM 5.0	EC002540

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Hexahydromethylphthalic-anhydride; Lead
REACH-SVHC CAS numbers	25550-51-0; 7439-92-1