


Push-in terminal block-UJ6-10JD - 421511



Push-in terminal block , connection method : spring connection , number of connections : 2 , crimping range : 1.5mm² -16 mm² , AWG : 16-6 , thickness : 10.2mm , height : 49.6mm , color : yellow-green , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	40
NW per piece(g)	32.8
Layers	1
Number of connections	2
Rated cross section(mm ²)	10
Color	yellow-green
Insulation material	PA
Flame retardant grade	V0
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Spring connection

Parameter	Data
Stripping length(mm)	17
Solid conductors(mm ²)	1.5-16
Solid conductors AWG	16-6
Stranded conductors(mm ²)	1.5-10
Stranded conductors AWG	16-8
Connection in acc. with standard	IEC 60947-7-1
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%

Dimension

Parameter	Data
Width(mm)	67.7
Thickness(mm)	10.2
Height(mm)	49.6