

Push-in terminal block - UJ6-35JD - 421519



Terminal block, connection method: spring connection, connection quantity: 2, crimping range: 6mm² -35mm², AWG: 10-2, thickness 16.2mm, height 58.6mm, color: yellow-green, mounting: TH35-7.5, TH35 -15 ;

Large wiring space to connect solid and stranded conductors without terminals , Compact design enables wiring in tight spaces

Product parameter

Parameter	Data
Technical data-Packing unit (PCS)	10
Technical data-NW per piece(g)	95
Technical data-layers	1
Technical data-Connections quantity	2
Technical data-rated cross section(mm ²)	35
Technical data-color	yellow-green
Technical data-Insulation Materials	PA
Technical data- Flame retardant grade	VO
Technical data-Insulation temperature	-40 ~ +125
Technical data-Wire feed	above the terminal
Technical data-Dimensions - Width(mm)	92
Technical data-Dimensions - Thickness(mm)	16.2
Technical data-Dimensions - Height(mm)	58.6
Technical data-Connection Data - Connection Method	Spring connection
Technical data-Connection data-Stripping length(mm)	24
Technical data-Connection data-Solid conductors(mm ²)	6-35
Technical data-Connection data-Solid conductorsAWG	10-2
Technical data-Connection data-Stranded conductors(mm ²)	6-35
Technical data-Connection data-Stranded conductorsAWG	10-2
Technical data-Environmental conditions- Operating temperature ()	-40 ~ +105
Technical data-Environmental conditions- Ambient temperature (storage/transportation) ()	-25 ~ +55

Parameter	Data
Technical data-Environmental conditions-Relative humidity	30% ~ 90%
Technical data-Standards and Specifications - Connections to Standards	IEC 60947-7-1