

DC/DC Converter

URB24_LD-50W(H)R3(A2S/A4S)

MORNSUN®

50W isolated DC-DC converter in DIP package
Ultra-wide input and regulated single output



FEATURES

- Ultra-wide 4:1 input voltage range
- High efficiency up to 91%
- I/O isolation test voltage 1.5K VDC
- Input under-voltage protection, output short-circuit, over-current, over-voltage protection
- Operating ambient temperature range: -40°C to +105°C
- Six-sided metal shielding package
- Industry standard pin-out
- Input reverse polarity protection available with chassis(A2S) or Din-Rail mounting (A4S) version



Patent Protection RoHS

URB24_LD-50WR3(A2S/A4S) series of isolated 50W DC-DC converter products with an ultra-wide 4:1 input voltage range. The feature efficiencies up to 91%, input to output isolation is tested with 1500VDC and the converter operate ambient temperature of -40°C to +105°C, input under-voltage protection, output over-voltage, over-current, short-circuit protection. They are ideally and widely used in applications such as industrial control, electric power, instruments and communications fields.

Selection Guide

Certification	Part No. ^①	Input Voltage ^④ (VDC)		Output		Full Load Efficiency ^③ (%) Min./Typ.	Capacitive Load (μF)Max.
		Nominal (Range)	Max. ^②	Voltage (VDC)	Current(mA) Max./Min.		
--	URB2412LD-50W(H)R3(A2S/A4S)	24 (9-36)	40	12	4167/208	89/91	3700
	URB2424LD-50W(H)R3(A2S/A4S)			24	2083/104	89/91	1000

Notes:

- ①Use "H" suffix for heat sink mounting, "A2S" suffix for chassis mounting and "A4S" suffix for DIN-Rail mounting. We recommend to choose modules with a heat sink for enhanced heat dissipation and applications with extreme temperature requirements;
- ②Exceeding the maximum input voltage may cause permanent damage;
- ③Efficiency is measured at nominal input voltage and rated output load; efficiencies for A2S and A4S Model's is decreased by 2% due to the input reverse polarity protection circuit;
- ④The minimum input voltage and starting voltage of A2S and A4S Model are 1VDC higher than those of DIP package due to input reverse polarity protection function.

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Current (full load / no-load)	Nominal input voltage	--	2289/60	2341/100	mA
Surge Voltage (1sec. max.)	Nominal input voltage & constant resistance load	-0.7	--	50	VDC
Start-up Voltage		--	--	9	
Input Under-voltage Protection		5.5	6.5	--	VDC
Start-up Time	Nominal input voltage & constant resistance load	--	10	120	ms
Input Filter		PI filter			
Hot Plug		Unavailable			
Ctrl*	Module on	Ctrl pin open or pulled high TTL (3.0-12VDC)			
	Module off	Ctrl pin pulled low to GND (0-1.2VDC)			
	Input current when off	--	6	12	mA

MORNSUN®

MORNSUN Guangzhou Science & Technology Co., Ltd.

Note: *The Ctrl pin voltage is referenced to input GND.

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Voltage Accuracy	5%-100% load	--	±1	±3	%
Linear Regulation	Input voltage variation from low to high at full load	--	±0.2	±0.5	
Load Regulation	5%-100% load	--	±0.5	±1	
Transient Recovery Time	25% load step change, nominal input voltage	--	250	500	μs
Transient Response Deviation	25% load step change, input voltage range	--	±3	±5	%
Temperature Coefficient	Full load	--	--	±0.03	%/°C
Ripple & Noise ^①	20MHz bandwidth, nominal input voltage, 5%-100% load	12V output 24V output	180 240	250 300	mV p-p
Trim	Input voltage range	90	--	110	
Over-voltage Protection		110	140	160	%Vo
Over-current Protection		110	140	200	
Short-circuit Protection		Continuous, self-recovery			

Note:

①The "parallel cable" method is used for Ripple and Noise test, please refer to DC-DC Converter Application Notes for specific information.

General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Isolation	Input-output Electric Strength Test for 1 minute with a leakage current of 1mA max.	1500	--	--	VDC
	Input/output-Case Electric Strength Test for 1 minute with a leakage current of 1mA max.	1000	--	--	
Insulation Resistance	Input-output resistance at 500VDC	100	--	--	MΩ
Isolation Capacitance	Input-output capacitance at 100KHz/0.1V	--	2200	--	pF
Operating Temperature	See Fig. 1	-40	--	+105	°C
Storage Temperature		-55	--	+125	
Storage Humidity	Non-condensing	5	--	95	%RH
Pin Soldering Resistance Temperature	Soldering spot is 1.5mm away from case for 10 seconds	--	--	+300	°C
Vibration		10-150Hz, 5G, 0.75mm. along X, Y and Z			
Switching Frequency ^①	PWM mode	--	300	--	KHz
MTBF	MIL-HDBK-217F@25°C	1000	--	--	K hours

Note:

①Switching frequency is measured at full load. The module reduces the switching frequency for light load (below 50%) efficiency improvement.

Mechanical Specifications

Case Material	Aluminum alloy		
Dimensions	Without heat sink	Horizontal package	50.80 x 25.40 x 11.80 mm
		A2S chassis mounting	76.00 x 31.50 x 21.20 mm
		A4S Din-rail mounting	76.00 x 31.50 x 25.80 mm
	With heat sink	Horizontal package	51.40 x 26.20 x 16.50 mm
		A2S chassis mounting	76.00 x 31.50 x 25.30 mm
		A4S Din-rail mounting	76.00 x 31.50 x 29.90 mm
Weight	Without heat sink	Horizontal package/A2S chassis mounting /A4S Din-rail mounting	39g(Typ.)/62g(Typ.)/82g(Typ.)
	With heat sink	Horizontal package/ A2S chassis mounting/ A4S Din-rail mounting	48g(Typ.)/71g(Typ.)/91g(Typ.)
Cooling Method	Free air convection		

Electromagnetic Compatibility (EMC)

Emissions	CE	CISPR32/EN55032	CLASS B (see Fig. 3-② for recommended circuit)	
	RE	CISPR32/EN55032	CLASS B (see Fig. 3-② for recommended circuit)	
Immunity	ESD	IEC/EN61000-4-2	Contact $\pm 4\text{KV}$	perf. Criteria B
	RS	IEC/EN61000-4-3	10V/m	perf. Criteria A
	EFT	IEC/EN61000-4-4	100KHz $\pm 2\text{KV}$ (see Fig. 3-① for recommended circuit)	perf. Criteria B
	Surge	IEC/EN61000-4-5	line to line $\pm 2\text{KV}$ (see Fig. 3-① for recommended circuit)	perf. Criteria B
	CS	IEC/EN61000-4-6	3 Vr.m.s	perf. Criteria A

Typical Characteristic Curves






Fig. 1



Design Reference


1. Typical application

All the DC-DC converters of this series are tested before delivery using the recommended circuit shown in Fig. 2. Input and/or output ripple can be further reduced by appropriately increasing the input & output capacitor values C_{in} and C_{out} and/or by selecting capacitors with a low ESR (equivalent series resistance). Also make sure that the capacitance is not exceeding the specified max. capacitive load value of the product.



Vout (VDC)	C_{in} (μ F)	C_{out} (μ F)
12	100 μ F/50V	
24		47 μ F/50V

2. EMC compliance circuit




Notes: We use Part ① in Fig. 3 for Immunity tests and Part ② for Emissions test.
Selecting based on needs.

Parameter description:

Model	Vin:24V
FUSE	Choose according to actual input current
C0	680 μ F/50V
LCM	2.2mH, recommended to use MORNSUN's FL2D-30-222
C1	330 μ F/50V
C2	4.7 μ F/50V
CY1, CY2	Y1 Safety capacitor 2.2nF/250VAC
C3	Refer to the C_{out} in Fig. 2

3. Trim Function for Output Voltage Adjustment (open if unused)



Trim resistor connections (dashed line shows internal resistor network)

Calculating Trim resistor values:

$$\begin{aligned} \text{up: } R_T &= \frac{\alpha R_2}{R_2 - \alpha} - R_3 & \alpha &= \frac{V_{ref}}{V_{o'} - V_{ref}} \cdot R_1 \\ \text{down: } R_T &= \frac{\alpha R_1}{R_1 - \alpha} - R_3 & \alpha &= \frac{V_{o'} - V_{ref}}{V_{ref}} \cdot R_2 \end{aligned}$$



RT = Trim Resistor value
 α = self-defined parameter
 $V_{o'}$ = desired output voltage

Vout(V)	R1(K Ω)	R2(K Ω)	R3(K Ω)	Vref(V)
12	10.90	2.87	15	2.5
24	24.77	2.87	5.1	2.5

4. The products do not support parallel connection of their output



5. For additional information please refer to DC-DC converter application notes on www.mornsun.cn

URB24_LD-50WR3 Dimensions and Recommended Layout



Pin-Out	
Pin	Mark
1	Ctrl
2	GND
3	Vin
4	+Vo
5	0V
6	Trim


URB24_LD-50WHR3 Dimensions and Recommended Layout




Pin-Out	
Pin	Mark
1	Ctrl
2	GND
3	Vin
4	+Vo
5	0V
6	Trim

URB24_LD-50WR3A2S Dimensions and Recommended Layout

THIRD ANGLE PROJECTION




Pin-Out						
Pin	1	2	3	4	5	6
Mark	Ctrl	GND	Vin	+Vo	0V	Trim




Note:
Unit: mm[inch]
Wire range: 24–12 AWG
Tightening torque: Max 0.4 N·m
General tolerances: ± 1.00[± 0.039]

URB24_LD-50WHR3A2S Dimensions and Recommended Layout

THIRD ANGLE PROJECTION




Pin-Out						
Pin	1	2	3	4	5	6
Mark	Ctrl	GND	Vin	+Vo	0V	Trim




Note:
Unit: mm[inch]
Wire range: 24–12 AWG
Tightening torque: Max 0.4 N · m
General tolerances: ± 1.00[± 0.039]

URB24_LD-50WR3A4S Dimensions and Recommended Layout

THIRD ANGLE PROJECTION




Pin-Out						
Pin	1	2	3	4	5	6
Mark	Ctrl	GND	Vin	+Vo	0V	Trim




Note:
Unit: mm[inch]
Mounting rail: TS35
Wire range: 24–12 AWG
Tightening torque: Max 0.4 N·m
General tolerances: ± 1.00[± 0.039]

URB24_LD-50WHR3A4S Dimensions and Recommended Layout

THIRD ANGLE PROJECTION



Pin-Out						
Pin	1	2	3	4	5	6
Mark	Ctrl	GND	Vin	+Vo	0V	Trim



Note:
Unit: mm[inch]
Mounting rail: TS35
Wire range: 24–12 AWG
Tightening torque: Max 0.4 N·m
General tolerances: ± 1.00[± 0.039]

Note:

1. For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging number: 58200035(without heat sink), 58200051(with heat sink), 58220022(A2S/A4S package);
2. Recommended used in more than 10% load, if the load is lower than 10%, then the ripple index of the product may exceed the specification, but does not affect the reliability of the product;
3. The maximum capacitive load offered were tested at input voltage range and full load;
4. Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^{\circ}\text{C}$, humidity<75%RH with nominal input voltage and rated output load;
5. All index testing methods in this datasheet are based on company corporate standards;
6. We can provide product customization service, please contact our technicians directly for specific information;
7. Products are related to laws and regulations: see "Features" and "EMC";
8. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China
Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: info@mornsun.cn www.mornsun-power.com