






REV	CONTENT	CHK	DATE
V0.0	CONTENT	CXL	20.05.20
V0.1	以实物修订图面	CXL	22.08.11

Electrical :

- 1.Rated Voltage : **UL 300V IEC 250V**
 2.Rated Current : **8A 7A**
 3.Withstanding Voltage : **AC1600V/1Min.**
 4.Operating Temperature : **-40°C~+105°C**
 5.RoHS Compliance
 6.Safty Approval : **UL CE**
 7."★" is the key quality control point

CUTOUT DIMENSIONS



① Sereies NO. ⑤ 1 Single Pitch
2 Double Pitch

② Pitch ⑥ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

④ CB--Wide Pin
⑦ Customer Request: 00--Standard

4	NUT	XX	2	BRASS	/
3	PIN-02	XX	N/2	BRASS	Tin Plated
2	PIN-01	XX	N/2	BRASS	Tin Plated
1	HOUSING	XX	1	PA66 UL94V-0	SEE NOTE
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	CXL	DATE	20.05.11	SIZE	A4 UNITS mm SHEET/OF 1 / 1
CHK.	DATE			SCALE	1:1
APP.	DATE			NAME	15EGTVC-3.81-XXP-CB-XX-00
				DWGNO.	XXXXX

Golten 宁波冠泰电子有限公司
 NINGBO GOLTEN ELECTRONICS CO., LTD.

Total Pitch Tolerances in mm									Nominal dimension range in mm									$\perp$		$\equiv$	---		//
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 0	over 10		over 0	over 100	over 150
to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10		all	to 100	to 150	
± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.44	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5