


Screw clamping terminal block-  
UKJ-4JD/L/L- 011311



Screw clamping terminal block, connection method : screw connection , number of connections : 5 , crimping range : 0.2mm<sup>2</sup> -4mm<sup>2</sup> , thickness:6.2mm , height:51.5mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

### Product parameter

Parameter	Data
Packing unit (PCS)	60
NW per piece(g)	/
Layers	3
Number of connections	5
Rated cross section(mm <sup>2</sup> )	4
Color	grey
Insulation material	PA
Flame retardant grade ( UL94 )	V0
Temperature of insulation material	-40 ~ +125
Wire feed	Both sides of the terminal

### Product certification

Parameter	Data
Certification logo	<b>CE</b>
Certification logo	<b>RoHS</b>

### Technical data

Parameter	Data
Connection Method	Screw connection

Parameter	Data
Screw thread	M3
Stripping length(mm)	9
Tightening torque	0.6-0.8Nm
Solid conductors(mm <sup>2</sup> )	0.2-4
Stranded conductors(mm <sup>2</sup> )	0.2-4
Operating temperature ( )	-40 ~ +105
Ambient temperature (storage/transportation) ( )	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

## Dimension

Parameter	Data
Width(mm)	88
Thickness(mm)	6.2
Height(mm)	51.5