



		尺寸公差(mm)				
		0	>30	>60	>100	0.05/10
Rated current	10A	~	~	~	~	±T
Rated voltage	300V	30	60	100	150	
Coil/Contact dielectric voltage	2000V/S	±0.20 ±0.30 ±0.50 ±0.70 ±1.00				
Dielectric voltage between contact	2000V/S					
Screw torque	1.2Nm					
External connection wire	20-14/0.5-2.5W					
Ambient temperature	G/mm ²					
Key controlled symbol	-40~+65℃					*
Conform to RoHS						

Printing for laser marking/printing content is clear ,no broken line/rect
 Seal literal reference according to the foot position in the drawing

REV	ECN	DESCRIPTION	DRAFT	DATE

1	DPTF08A-3-00A(H)-N	30019000034	1		
MATERIAL: /		SURFACE: /			
MATERIAL NO.:		30020000053			
STATUS:		/			
APPD:		Description:			
CHKD:		NINGBO DEGSON ELECTRICAL CO., LTD			
DRAFT:		DRAWING NO.:			
/		30000361			
SIZE: A4		TYPE: PRODUCT DRAWING		SCALE: 1:1	REV
/		/		1/1	TO-1
/		/		1/1	1/1

1 2 3 4 5 6

D C B A