

Screw clamping terminal block-
USK-16JD-281014



Screw clamping terminal block, connection method : screw connection , number of connections : 2 , crimping range : 2.5mm² -16mm² ,AWG : 14-6 , thickness:12mm , height:48mm , color : yellow-green , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

| Parameter | Data |
|---------------------------------------|---------------|
| Packing unit (PCS) | 30 |
| NW per piece(g) | 41.8 |
| Layers | 1 |
| Number of connections | 2 |
| Rated cross section(mm ²) | 16 |
| Color | yellow-green |
| Insulation material | PA |
| Flame retardant grade (UL94) | V0 |
| Temperature of insulation material | -40 ~ +125 |
| Wire feed | Terminal side |

Product certification

| Parameter | Data |
|--------------------|-------------|
| Certification logo | CE |
| Certification logo | RoHS |

Technical data

| Parameter | Data |
|---|------------------|
| Connection Method | Screw connection |
| Screw thread | M4 |
| Stripping length(mm) | 12 |
| Tightening torque | 2.0-2.4 |
| Solid conductors(mm ²) | 2.5-16 |
| Solid conductors AWG | 14-6 |
| Stranded conductors(mm ²) | 2.5-16 |
| Stranded conductors AWG | 14-6 |
| Operating temperature () | -40 ~ +105 |
| Ambient temperature (storage/transportation) () | -25 ~ +60 |
| Relative humidity | 30% ~ 90% |
| Connection in acc. with standard | IEC 60947-7-1 |

Dimension

| Parameter | Data |
|---------------|------|
| Width(mm) | 57 |
| Thickness(mm) | 12 |
| Height(mm) | 48 |