



# Heyco® Rubber Grommets

Mounting Diameter: 0.250" to 0.562"

- Used to protect or cover through holes. Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 160 sizes available that will accommodate mounting holes ranging from .250" (6,4 mm) to holes as large as 2.50" (63,5 mm) diameter and panel thicknesses from .063" (1,6 mm) to .375" (9,5 mm).
- Rubber grommets are constructed of SBR with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS						
Maximum Thickness		Mounting Hole Diameter				Black	A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.063	6,4	.250	6,4	<b>G1004</b>	RG 250-4-2	.125	3,2	.344	8,7	.188	4,8	
.063	6,4	.250	6,4	<b>G1005</b>	RG 250-5-2	.156	4,0	.375	9,5	.188	4,8	
.063	6,4	.250	6,4	<b>G1006</b>	RG 250-5-2A	.156	4,0	.438	11,1	.375	9,5	
.094	2,4	.281	7,1	<b>G1010</b>	RG 281-6-3	.188	4,8	.438	11,1	.219	5,6	
.063	1,6	.312	7,9	<b>G1017</b>	RG 312-6-2	.188	4,8	.406	10,3	.219	5,6	
.063	1,6	.312	7,9	<b>G1018</b>	RG 312-6-2A	.188	4,8	.438	11,1	.188	4,8	
.063	1,6	.312	7,9	<b>G1019</b>	RG 312-6-2B	.188	4,8	.500	12,7	.250	6,4	
.094	2,4	.312	7,9	<b>G1014</b>	RG 312-6-3	.188	4,8	.500	12,7	.281	7,1	
.125	3,2	.312	7,9	<b>G1020</b>	RG 312-6-4	.188	4,8	.438	11,8	.250	6,4	
.188	4,8	.312	7,9	<b>G1022</b>	RG 312-6-6	.188	4,8	.438	11,8	.313	8,0	
.250	6,4	.312	7,9	<b>G1023</b>	RG 312-6-8	.188	4,8	.438	11,8	.375	9,5	
.063	1,6	.312	7,9	<b>G1026</b>	RG 312-7-2	.219	5,6	.438	11,8	.188	4,8	
.094	2,4	.375	9,5	<b>G1033</b>	RG 375-4-3	.125	3,2	.500	12,7	.313	8,0	
.188	4,8	.375	9,5	<b>G1034</b>	RG 375-6-6	.188	4,8	.625	15,9	.375	9,5	
.063	1,6	.375	9,5	<b>G1037</b>	RG 375-8-2	.250	6,4	.563	14,3	.250	6,4	
.094	2,4	.375	9,5	<b>G1038</b>	RG 375-8-3	.250	6,4	.500	12,7	.250	6,4	
.094	2,4	.375	9,5	<b>G1039</b>	RG 375-8-3A	.250	6,4	.563	14,3	.281	7,1	
.063	1,6	.375	9,5	<b>G1042</b>	RG 375-9-2	.281	7,1	.563	14,3	.250	6,4	
.375	9,5	.375	9,5	<b>G1043</b>	RG 375-10-12	.313	8,0	.563	14,3	.500	12,7	
.125	3,2	.406	10,3	<b>G1047</b>	RG 406-9-4	.281	7,1	.625	15,9	.375	9,5	
.063	1,6	.437	11,1	<b>G1052</b>	RG 437-8-2	.250	6,4	.625	15,9	.188	4,8	
.063	1,6	.437	11,1	<b>G1053</b>	RG 437-8-2A	.250	6,4	.625	15,9	.313	8,0	
.125	3,2	.437	11,1	<b>G1056</b>	RG 437-8-4	.250	6,4	.625	15,9	.250	6,4	
.188	4,8	.437	11,1	<b>G1057</b>	RG 437-8-6	.250	6,4	.625	15,9	.313	8,0	
.250	6,4	.437	11,1	<b>G1058</b>	RG 437-8-8	.250	6,4	.625	15,9	.375	9,5	
.063	1,6	.437	11,1	<b>G1061</b>	RG 437-10-2	.313	8,0	.625	15,9	.281	7,1	
.094	2,4	.437	11,1	<b>G1062</b>	RG 437-10-3	.313	8,0	.625	15,9	.313	8,0	
.250	6,4	.500	12,7	<b>G1086</b>	RG 500-10-8	.313	8,0	.625	15,9	.625	15,9	
.063	1,6	.500	12,7	<b>G1089</b>	RG 500-12-2	.375	9,5	.625	15,9	.250	6,4	
.063	1,6	.500	12,7	<b>G1090</b>	RG 500-12-2A	.375	9,5	.688	17,5	.281	7,1	
.125	3,2	.500	12,7	<b>G1092</b>	RG 500-12-4	.375	9,5	.625	15,9	.313	8,0	
.125	3,2	.500	12,7	<b>G1093</b>	RG 500-12-4A	.375	9,5	.625	15,9	.406	10,3	
.156	4,0	.500	12,7	<b>G1094</b>	RG 500-12-5	.375	9,5	.688	17,5	.313	8,0	
.250	6,4	.500	12,7	<b>G1095</b>	RG 500-12-8	.375	9,5	.750	19,1	.500	12,7	
.375	9,5	.500	12,7	<b>G1096</b>	RG 500-12-12	.375	9,5	.625	15,9	.625	15,9	
.188	4,8	.562	14,3	<b>G1110</b>	RG 562-6-6	.188	4,8	.750	19,1	.312	7,9	
.063	1,6	.562	14,3	<b>G1112</b>	RG 562-10-2	.313	8,0	.813	20,7	.313	8,0	
.125	3,2	.562	14,3	<b>G1114</b>	RG 562-10-4	.313	8,0	.813	20,7	.375	9,5	
.188	4,8	.562	14,3	<b>G1115</b>	RG 562-10-6	.313	8,0	.813	20,7	.375	9,5	
.188	4,8	.562	14,3	<b>G1116</b>	RG 562-10-6A	.313	8,0	.813	20,7	.438	11,1	

Standard color black.

