


UDK-PLC-RI 24Vac/dc-328003



Relay coupling, voltage input: 24V, current input: about 11mA, connection methods: screw connection, pollution degree: 2, AWG: 26-14, current input: 6A, width 80mm, thickness 6.2mm, color: grey, mounting rail: TH35.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	/
Cross section(mm ²)	0.14-2.5
Color	grey
Materials	PA66
Flame retardant rating	V0
Voltage input(V)	24V
Current input(mA)	about 11mA
Insulation material temperature	-40 ~ +125
Connection methods	screw connection

Product certification

Parameter	Data
Certification logo	CE
Certification logo	

Parameter	Data
	

Technical data

Parameter	Data
Connection methods	screw connection
Current output (A)	6A
Upper switching voltage (V)	250V
Rated power(W)	140
Coils/contacts	4000V
Contact material	AgNi
Resistive load	1500V
Ambient temperature ()	-25 ~ +60
Storage temperature (Storage/transportation) ()	-30 ~ +80
Relative humidity	5% ~ 85%
Connection in acc. with standard	IEC 60947-5-1
Pollution degree	2

Dimension

Parameter	Data
Width(mm)	80
Thickness(mm)	6.2
Height(mm)	94